



XRN-815S

8CH NVR



Key Features

- Up to 8CH, 12MP camera supported
- H.265, H.264, MJPEG codec
- AI Search: Object Attribute (When integrated with Wisenet AI Camera)
- 100Mbps network camera recording
- Plug & play by 8 PoE(LAN, 10/100), 1PoE(WAN, 1Gbps)
- SATA 2ea(up to 20TB)
- ARB supported
- P2P service (QR code connect) supported

XRN-815S

8CH NVR



Specifications

Display		
Network camera	Inputs	Max. 8CH
	Resolution	12MP ~ CIF
	Protocols	SUNAPI, ONVIF
Decoding	Local Display	HDMI1: 3840x2160(30Hz), HDMI2: 1920x1080(60Hz)
	Multi Screen Display	Clone Mode : Dynamic layout Expand Mode : HDMI1 Dynamic layout,HDMI2 up to 9 Div. [Web] 1/ 2H/ 2V/ 3V/ 4/ 6/ 8/ 9
	Resolution	[Local Monitor] 12M(30fps), 8M(600fps), 1080p(240fps), 720P(240fps), D1(480fps)
Performance		
Operating System	Embedded	Linux
Record	Compression	H.265, H.264, MJPEG
	Recording Bandwidth	Max. 100Mbps
	Resolution	8MP ~ CIF
	Mode	Normal, Dual Stream, Schedule(Continuous/Event), Event (Pre/Post), Bookmark
	Event Trigger	Alarm Input, Video Loss, Camera Event(Sensor, MD, Video Analytics, Defocus, Audio), Dynamic Event, User Event
	Event Action	e-Mail, Event Push, PTZ Preset, Alarm Out, Buzzer, Monitor Out, FTP, SUNAPI Command, Shutdown
Search & Play	Playback Bandwidth	Max. 32Mbps
	User	Max. 4 Users (Local 1, Remote 3)
	Simultaneous playback	Max. 32CH(Local 8CH, Remote 8CH per user)
	Fisheye Dewarping	CMS
	Mode	Date & Time(Calendar), Event list, Text Search, Smart Search
	Resolution	CIF ~ 12MP
	Playback Control	Fast/Slow Forward / Backward, Move one step Up / Down
Storage	Supported HDD	Up to 10TB
	HDD Slot	SATA 2ea(Max. 20TB)
Backup	File backup	BU/Exe/AVI(GUI), JPG/AVI(Network)
	Function	Multi channel(Up to 8CH) Play, Date-Time/Title display

Network

Protocol		IPv4, IPv6, TCP/IP, UDP/IP, RTP (UDP), RTP (TCP), RTSP, NTP, HTTP, DHCP (Server, Client), SMTP, ICMP, IGMP, ARP, DNS, DDNS, uPnP, HTTPS, SNMP, ONVIF (Profile-S), SUNAPI(Server, Client)
DDNS		Hanwha DDNS
Transmission Bandwidth		Max. 120Mbps
Audio	Input/Output	8 CH(network)
	Compression	G.711, G.726, AAC(16/48KHz)
	Audio Communication	2-Way
Max Remote Users		Search(3), Live Unicast(10), Multicast(20)
Security		IP address filtering, User access Log, 802.1x, Encryption Device certificate(Hanwha Techwin Root CA), Signed firmware
Web viewer	Supported OS	Windows 10, macOS 11
	Supported browser	Google Chrome, Microsoft Edge, Mac Safari
Viewer Software		WAVE, SSM, Webviewer, Smart Viewer, Wisenet mobile Support CGI(SUNAPI) for integration to 3'rd party VMS

Function

Camera Setup	Register	Auto, Manual
	Item	IP address, Add profile edit, Bitrate, Compression, GOP, Quality, Camera MD setup (4, 8 point polygon) Camera video setup (Simple focus, Brightness/Contrast, Flip/Mirror, IRIS, WDR, D&N, SSNR, Shutter, SSSDR, DIS),, Fisheye Dewarping Mode, Hallway View Setup, Camera Webpage
PTZ	Control	Via GUI, Webviewer
	Preset	300 Presets
Smart phone	Support Model	iOS, Android
	Protocol Support	RTP, RTSP, HTTP, CGI(SUNAPI)
	Control	Live: Multi-Profile Support, Multi Channel Playback
	Max. Remote Users	Search(3), Live Unicast(10)
Redundancy	Failover	N+1
	ARB	Support
Easy configuration		P2P(QR code)

Interface

Front	Indicator	Power, Record, Network
Storage		OK
Reset		Support
HDMI		2EA
Audio		Out 1EA (RCA output)
Ethernet		PoE+ RJ-45(LAN, 10/100) 8ea, RJ-45 1ea (WAN, 1Gbps)
Alarm		In 4EA, Out 2EA

Interface

USB	3EA(Front 2 x USB 2.0, Rear 1 x USB 3.0)
Power inlet	AC 1EA

System

Log	Log List	Max. 100,000 (System Log, Event Log each)
System Control		Mouse, Keyboard, Web
Language		English, French, German, Italian, Spanish, Russian, Turkish, Polish, Dutch, Czech, Portuguese, Danish, Rumanian, Serbian, Croatian, Hungarian, Greek, Norwegian, Finnish, Korean, Chinese, Japanese, Thai, Vietnamese

Environmental

Operating Temperature	0°C to +40°C(32°F to 104°F)
Operating Humidity	20% ~ 85% RH

Electrical

Power Input	100 ~ 240 VAC ±10%, 50/60Hz
Power Consumption	Max. 165W(563 BTU with 2HDD, PoE On)
Power Consumption w/o PoE	35W
PoE Budget	100W

Mechanical

Color / Material	Black / Metal
Dimension	370.0 x 50.7 x 320.0 mm (14.57 x 2.00 x 12.60 inch)
Weight	2.86Kg(6.31lb)

Intelligent Analysis

AI Search	Object Attribute	Compatible with Hanwha AI Cameras
-----------	------------------	-----------------------------------

XRN-815S

8CH NVR



CAD

Unit: mm [inch]

