



DFx-37-HD



FEATURES

- 1080p AHD resolution
- 3.7mm wide-angle lens
- Two piece construction for easy installation
- Fits most standard door frames (mullions)
- Durable aluminum construction
- Curved surface with 180° FOV adjustment
- White, black and silver housing options
- 12VDC (4" models) or 24 VAC (6" models)



Door Frame Camera



1080p Resolution

3.7mm wide angle lens



180° Camera

Curved surface for easy adjustment



Fits on Door Frame

Capture quality facial images




Ideal for Retail

Install on entry and exit doors

SPECIFICATIONS

Models	DFS-37-HD (silver), DFB-37-HD (black), DFW-37-HD (white)	DFS-37-24HD (silver), DFB-37-24HD (black), DFW-37-24HD (white)
Image Sensor	1/3" CMOS	
Effective Pixels	1944 (H) X 1080 (V)	
Scanning System	Progressive Scan	
Resolution	1080p @ 30 FPS, 720P @ 30FPS	
Min. Illumination	0.1 lux @ F2.5, 30 IRE	
Lens	3.7mm Pinhole, F2.5	
HFOV	66°	
DSP Features	3D-DNR, Sens-up, D-WDR	
Frame Rate	30fps	
Power Supply	12VDC	24VAC
Power Consumption	130mA max	Max. 80mA
Operating Temperature	14° ~ 122° F (-10° ~ 50° C)	
Ambient Humidity	90% RH	
Dimensions	4" H x 1.7" W x 1.4" D	6" H x 1.7" W x 1.4" D
Construction	Aluminum, powder coated	

DIMENSIONAL DRAWINGS (6" Models)



Specifications are subject to change without notice.