


Carrying Case
Includes:

- Fiber Optic Light Source
- Instruction Manual
- (3) AA Batteries (required for operation)
- (2) Cleaning Swabs
- Protective Carrying Case
- FC/UPC Adapter
- SC/UPC Adapter
- ST/UPC Adapter
- FC-LC/UPC Adapter (Singlemode Only)

The perfect tool for providing a stable light source for single mode fiber measurements.

- Highly stable output power and wavelengths
- Four different modulation outputs (CW, 270 Hz, 1 kHz, 2 kHz) at 1310 nm and 1550 nm wavelengths
- Intelligent backlight control reduces power consumption
- Auto-off function can be turned on or off
- Automatic wavelength detection function
- SC, ST, FC & FC-LC adapters included
- PC/UPC adapters included
- Color LCD Display
- Backside Kickstand

SPECIFICATIONS	
WAVELENGTH (nm)	1310/1550 ±20
SPECTRAL WIDTH (nm)	≤5
TYPICAL OUTPUT (dBm)	-7
STABILITY (dB, 15 min)¹	≤0.05
TYPICAL OUTPUT POWER ADJUSTABLE RANGE (dB)	-5 ~ -12
MODULATION FREQUENCY (Hz)	CW, 270, 330, 1K, 2K
INTERFACE TYPE	FC/SC/ST/FC-LC (UPC)
DISPLAY SIZE	2.4-inch LCD
POWER SUPPLY	1.5V* 3 AA alkaline batteries
AUTO-OFF (min)	10
CONTINUOUS WORKING HOURS (hr)²	≥25
OPERATING TEMPERATURE (°C)	-10 ~ +60
STORAGE TEMPERATURE (°C)	-25 ~ +70
DIMENSIONS	7.44" x 3.31" x 1.85" (189 mm x 84 mm x 47 mm)
WEIGHT	0.64 lb (290 g)
UPC #	811490018655

