



Network

Dome

TNV-8011C

5MP Corner Mount Camera

FC |  | CE | EAC

Key Features

- Maximum 5MP resolution
- Maximum 30fps @ all resolutions (H.265/H.264/MJPEG)
- 0.1lux@F2.3(Color), 0.02lux@F2.3(B/W)
- 2.3mm fixed focal
- Anti-ligature design for corrections and behavioral health facilities
- Day & Night Auto(ICR), WDR (120dB)
- Defocus detection, Tampering, Audio detection
- Micro SD/SDHC/SDXC memory slot (128GB)
- Hallway view, WiseStream II support
- PoE, IP66, IP6K9K, IK10

Compatible Accessories (Optional)



SBC-170CB



SBC-170CW



SBC-170C

TNV-8011C

5MP Corner Mount Camera



Specifications

Video

Imaging Device	1/2.8" CMOS
Resolution	2592x1944, 1920x1080, 1280x960, 1280x720, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360
Max. Framerate	H.265/H.264: Max. 30fps/25fps(60Hz/50Hz) MJPEG: Max. 15fps/12fps (60Hz/50Hz)
Min. Illumination	Color: 0.1 lux (F2.3, 1/30sec) B/W: 0.02 lux (F2.3, 1/30sec)
Video Out	CVBS: 1.0 Vp-p / 75Ω composite, 720x480(N), 720x576(P) for installation USB: Micro USB Type B, 1280x720 for installation

Lens

Focal Length (Zoom Ratio)	2.3mm fixed focal
Max. Aperture Ratio	F2.3
Angular Field of View	H: 131° / V: 93.4° / D: 174°
Focus Control	Fixed

Operational

Camera Title	Displayed up to 85 characters
Day & Night	Auto(ICR)
Backlight Compensation	BLC, WDR, SDR
Wide Dynamic Range	120dB
Digital Noise Reduction	SSNR
Digital Image Stabilization	Support
Defog	Support
Motion Detection	4ea, polygonal zones
Privacy Masking	6ea, rectangular zones
Gain Control	Low / Middle / High
White Balance	ATW / AWC / Manual / Indoor / Outdoor(include Mercury & Sodium)
LDC	Support
Electronic Shutter Speed	Minimum / Maximum / Anti flicker (2~1/12,000sec)
Video Rotation	Flip, Mirror, Hallway view(90°/270°)
Analytics	Defocus detection, Directional detection, Motion detection, Enter/Exit, Tampering, Virtual line, Audio detection
Alarm I/O	Input 1ea / Output 1ea
Alarm Triggers	Analytics, Network disconnect, Alarm input
Alarm Events	File upload via FTP and e-mail Notification via e-mail SD/SDHC/SDXC or NAS recording at event triggers Alarm output
Audio In	Selectable(mic in/line in) Supply voltage: 2.5VDC(4mA), Input impedance: 2K Ohm
Audio Out	Line out. Max.output level: 1Vrms

Network

Ethernet	RJ-45(10/100BASE-T)
Video Compression	H.265/H.264: Main/Baseline/High, MJPEG

Audio Compression	G.711 u-law /G.726 selectable G.726(ADPCM) 8KHz, G.711 8KHz G.726: 16Kbps, 24Kbps, 32Kbps, 40Kbps
Smart Codec	Manual(5ea area), WiseStream II
Bitrate Control	H.264/H.265: CBR or VBR MJPEG: VBR
Streaming	Unicast (6 users) / Multicast Multiple streaming (Up to 3 profiles)
Protocol	IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour, sRTP
Security	HTTPS(SSL) login authentication Digest login authentication IP address filtering User access log 802.1X authentication(EAP-TLS, EAP-LEAP) Device certificate(Hanwha Techwin Root CA)
Application Programming Interface	SUNAPI(HTTP API) Wisenet open platform

General

Webpage Language	English, Korean, Chinese, French, Italian, Spanish, German, Japanese, Russian, Swedish, Portuguese, Czech, Polish, Turkish, Dutch, Hungarian, Greek
Edge Storage	Micro SD/SDHC/SDXC 1slot 128GB
Memory	512MB RAM, 256MB Flash

Environmental & Electrical

Operating Temperature / Humidity	-10°C~+55°C(+14°F~+131°F) / Less than 95% RH
Storage Temperature / Humidity	-50°C~+60°C(-58°F~+140°F) / Less than 95% RH
Certification	IP66, IP6K9K, IK10
Input Voltage	PoE(IEEE802.3af, Class2)
Power Consumption	PoE: Max 6.49W, typical 4.6W,

Mechanical

Color / Material	White / Aluminium
RAL Code	RAL9003
Product Dimensions / Weight	170(W)x165(H)x78.8(D)mm(6.69x6.49x3.10") / 830g(1.83lb)
Skin Cover	SBC-170C, SBC-170CB, SBC-170CW

DORI (EN62676-4 standard)

Detect (25PPM/ 8PPF)	23.6m(77.51ft)
Observe (63PPM/ 19PPF)	9.4m(31.00ft)
Recognize (125PPM/ 38PPF)	4.7m(15.50ft)
Identify (250PPM/ 76PPF)	2.4m(7.75ft)


TNV-8011C

5MP Corner Mount Camera



CAD

Unit: mm [inch]



3		
2		
1	TNV-8011C	'21.11.23
No.	MODEL NAME	DATE
Unit:mm[inch]		SCALE:1/1
Hanwha Techwin		

© Hanwha Techwin Co.,Ltd. All rights reserved.