






Comparison Table for GV-IP Speaker

Models	GV-IPSC10	GV-IPSC10 V2.0	GV-IPSH30	GV-IPSH30 V2.0	GV-IPSS40	GV-IPSS40 V2.0
						
Audio						
Audio Format	PCM (uncompressed format)					
Rated Output	Built-in 2 * 15 W digital amplifier; one amplifier output can be connected to an external fixed-resistance speaker (4 ~ 16 ohms, within 15 W power)		Built-in 30 W digital amplifier		Built-in 40 W digital amplifier	
Speaker Unit	6.5" woofer + 0.75" tweeter		1.5" tweeter		4 x 4" woofer + 1 x 2" tweeter	
Rated Power of Speaker Unit	10 W		30 W		40 W	
Speaker Sensitivity (1 W / 1 m)	90 dB		108 dB		92 dB	
Max SPL (Rated / 1 m)	100 dB		123 dB		114 dB	
Speaker Frequency Range (-10 dB)	100 Hz ~ 20 kHz		300 Hz ~ 8 kHz		150 Hz ~ 18 kHz	
Network						
Network Interface	RJ-45 connector, 10/100 Ethernet					
Protocol	TCP/IP, UDP, IGMP, ICMP, ARP, SIP, ONVIF					
General						
Usage	Indoor		Outdoor		Outdoor	
Operating Temperature	-20°C ~ 60°C (-4°F ~ 140°F)		-25°C ~ 55°C (-13°F ~ 131°F)		-20°C ~ 60°C (-4°F ~ 140°F)	
Operating Humidity	10% ~ 90%		≤95%		10% ~ 90%	
Power Consumption	≤ 40 W		≤ 40 W		≤ 50 W	
Dimensions	Ø 200 x 100 mm (7.87" x 3.94")		285 x 205 x 285 mm (11.22" x 0.87" x 11.22")		150 x 635 x 95 mm (5.91" x 25" x 3.74")	
Net Weight	1.2 kg (2.65 lb)		2.0 kg (4.41 lb)		4.2 kg (9.26 lb)	
Input Power	DC 24V; 24V PoE (PoE splitter required)	DC 24V, 3.75A; PoE+ (IEEE 802.3at)	DC 24V; 24V PoE (PoE splitter required)	DC 24V, 3.75A; PoE+ (IEEE 802.3at)	DC 24V; 24V PoE (PoE splitter required)	DC 24V 3.75A; PoE+ (IEEE802.3at)
PoE Support	Yes (PoE splitter* required)	Yes	Yes (PoE splitter* required)	Yes	Yes (PoE splitter* required)	Yes
Audio Input Interface	2P Phoenix terminal		N/A		3.5 mm AUX IN	
Ingress Protection	N/A		IP66		N/A	

Note:

1. The PoE splitter* (PD2402G) is compatible with IEEE 802.3at with max. 24W power output.
2. All specifications are subject to change without prior notice.