

NK-1200

Network Keyboard



- Remote control of NVRs, network video transmitters, network video receivers and network cameras via the network connection
 - Convenient firmware upgrades via either the USB port or Ethernet
 - Programmable by using the LCD screen
- Two-way audio communication
 - Firmware duplication and auto-recovery functions to enhance system stability
- Two-way audio communication
 - Management of multiple network keyboards via the network connection

SPECIFICATIONS

Communication	
Interface	2 x RS485(Terminal Block), 10/100/1000 Ethernet(RJ45 PoEIEEE802.3Af)
Baud Rate	300 bps ~ 115,200bps
Supports protocols	Over 70 sorts of PTZprotocol(IDIS PANASONICPELCO SAMSUNGetc.)
Supports Devices	IP Camera,NVR, IDISsolution Suite
Display	LCD(2 Line)
USB	1x USB2.0 1x USB3.0
Audio in/out	1(3.5mm) / 1(3.5mm)
configuration	Joystick+ Main Control Board
S/W Upgrade	USB Network
SETUP Program	IDISDiscovery
General	
Dimension(W x H x D)	376.9mmx 95mm x 177.6mm(15.0" x 3.7" x 7.0")
Unit Weight(Kg)	1.1kg(2.43lb)
Operating Temperature	0℃ ~ 40℃ (32°F ~ 104°F)
Power Input	DC48V, 1A PoE(IEEE802.3af class0)
Approvals	FCCCE KC



PRODUCT IMAGE



DIMENSIONS

