

PIOB-0100

6 Digital Input and 6 Digital Output Network I/O Module



► Specifications

Device

Original Manufacturer	Advantech
Product Type	Network IO Module
Original Model	ADAM-6060
Description	6 Digital Input and 6 Digital Output Network I/O Module

Network

Network Protocol & Service	TCP, IP, UDP, HTTP, DHCP
Ethernet Port	Non-PoE: 1 port(s), Ethernet (10/100 Base-T), RJ-45 connector

Integration

Unified Solution	Fully compatible with NVR 3 Corporate
------------------	---------------------------------------

Interface

Serial Port	1 x RS-485/RS-422/RS-232
Digital Input/Output	6/6





General

Power Source	DC 10-30V
Weight	216.5g (0.477lb)
Dimensions	(W x H x D): 122mm x 27mm x 70mm (4.8" x 1.06" x 2.75")

Operating Temperature	-20°C ~ 70°C (-4°F ~ 158°F)
Storage Temperature	-30 °C ~ 80 °C (-22 °F ~ 176 °F)
Approvals	CE, FCC
Warranty	1 Year(s)

► Related Products

NVR - Standalone NVR

INR-340		<p>64-Channel 6-Bay RAID Tower Standalone NVR with Additional Computing Power, Recording Throughput 300 Mbps, Instant Playback, e-Map, HDMI, VGA and Display Port, Remote Access, Video Export, 64-Channel Synchronized Playback, 32-channel free license included (for ACTi video devices) and additional license required (for integration with POS, access control and extended devices), Supports External Storage (eSATA, iSCSI), Hardware RAID 0,1,5,10, 6-Bay (Storage Disks not included), Audio, AC 100-240V</p>
MNR-310		<p>32-Channel 2-Bay Transportation Standalone NVR with Recording Throughput 192 Mbps, Instant Playback, e-Map, HDMI and VGA Port, Remote Access, Video Export, 32-Channel Synchronized Playback, 16-channel free license included (for ACTi video devices) and additional license required (for integration with POS, access control and extended devices), Supports External Storage (eSATA, iSCSI), Software RAID 0,1, 2-Bay (Storage Disks not included), Wireless (Optional), DC 9-36V/AC 100-240V, e-Mark</p>
MNR-320P		<p>16-Channel 1-Bay GPS Transportation Standalone NVR with 4-port PoE Connectors, with Recording Throughput 192 Mbps, Instant Playback, e-Map, Shock Detection with built-in G-sensor, HDMI and VGA Port, Remote Access, Video Export, 16-Channel Synchronized Playback, 16-channel free license included (for ACTi video devices) and additional license required (for integration with POS, access control and extended devices), 1-Bay (Storage Disks not included), Wireless (Optional), Audio, DI/DO, DC 9-36V, e-Mark</p>
MNR-330P		<p>16-Channel 1-Bay GPS Transportation Standalone NVR with 4-port PoE Connectors, Additional Computing Power, with Recording Throughput 192 Mbps, Instant Playback, e-Map, Shock Detection with built-in G-sensor, HDMI and VGA Port, Remote Access, Video Export, 16-Channel Synchronized Playback, 16-channel free license included (for ACTi video devices) and additional license required (for integration with POS, access control and extended devices), 1-Bay (Storage Disks not included), Wireless (Optional), Audio, DI/DO, DC 9-36V, e-Mark</p>

