



FEATURES :

- Complies with the IEEE802.3 Ethernet, IEEE802.3u Fast Ethernet and IEEE 802.3ab Gigabit Ethernet Standards
- 16 /24 Port 10/100/1000M (Auto-negotiation) Switch
- 19" rack-mount size
- Non-blocking & Non-head-of-line blocking full wire speed forwarding
- Store-and-forward operation support
- Supports 9.6 KB JUMBO packet
- Provides 8K MAC address entry
- Supports broadcast storm filtering
- All ports provide Auto-Negotiation and Auto-MDI/ MDI-X functions
- Supports flow control: Back pressure for Half-duplex and IEEE 802.3x for Full-duplex mode
- Smart plug & play

SPECIFICATION :

Standards	IEEE 802.3 10BaseT / IEEE 802.3u 100BaseTX / IEEE 802.3ab 1000BaseT / IEEE 802.3x Flow control
Filtering/Forwarding Rates	1000Mbps port - 1,488,000pps / 100Mbps port - 148,800pps / 10Mbps - 14,880pps
Transmission Media	10BaseT Cat. 3, 4, 5 UTP/STP / 100BaseTX Cat. 5 UTP/STP / 1000BaseT Cat. 5E UTP/STP
LED Indicators	Per Port: LINK/ACT, 1000M / Per Unit: Power
Power Requirement	90 - 260V/AC, 50 - 60Hz
Power Consumption"	20 Watts (Max)
Dimensions	440 x 220 x 44 mm (L x W x H)
Weight	2.9 kg /3 kg
Operating Temperature	0 to 45°C
Storage Temperature	-20 to 90°C
Humidity	10 to 90% RH (non-condensing)
Certifications	FCC Class B, CE
FE/GE	GE
RJ-45 Port	24
Buffer Memory	500 Kbits
MAC Address Table Size	8K
Switching Capacity	48Gbps

DIMENSIONS : (Unit : mm)

440 x 220 x 44

