

Electronic Technical Services Inc. 211 Conchas SE Albuquerque, NM 87123 PH 505-888-3923 FAX 505-888-3926 Website: www.etsnm.com

SMI8 Eight Channel Microphone Interface Adapter

Description

Powers up to 8 ETS SM1 series microphones and distributes their audio outputs to individual RCA (or optional 3.5mm) jacks. Designed for connecting SM1 series microphones to equipment with un-balanced, line level inputs. Ideal for use with DRVs, remote monitoring equipment and multiple CCTV monitors (with built in speakers).



Includes

- SMI8 Interface adapter.
- 15 Vdc 800ma AC adapter.
- 8 6' RCA Patch cords.
- Installation instructions.

Options

 Add –RCA or –FL (Flying Leads) to P/N for alternate output cables.

Wiring Requirements

 Microphone cable runs: Stranded 22gauge, 2-conductor shielded cable.
Distances up to 1000 feet each.

SMI8 Interface Adapter Specifications

- RCA output jacks.
- Line level (0db) output levels.
- Terminal block microhone connections.
- LED power indicator.
- Power:12 VDC @ 80mA
- Reverse polarity protected.
- PPTC fused.
- Black plastic ABS housing.
- Dimensions: L 5.3 x W 3.3 x H 1.6
- Weight .17kg

Caution

It is the responsibility of the installation company and end user to comply with state and federal privacy laws regarding the use of audio surveillance equipment. If you are unfamiliar with these laws, consult a qualified attorney. In most cases, posting the provided warning labels in plain view is all that is required.