



| TS-855X-8G | |
|-----------------------------------|--|
| CPU | Intel ® Atom® C5125 8-core processor, 2.8GHz |
| CPU Architecture | 64-bit x86 |
| Floating Point Unit | Yes |
| Encryption Engine | Yes (AES-NI) |
| System Memory | 8 GB non-ECC UDIMM DDR4 (1 x 8 GB) |
| Maximum Memory | 128 GB (4 x 32 GB) |
| Memory Slot | 4 x U-DIMM DDR4 Support ECC memory |
| Flash Memory | 5GB (Dual boot OS protection) |
| Drive Bay | 6 x 3.5-inch + 2 x 2.5-inch SATA 6Gb/s, 3Gb/s |
| Drive Compatibility | 3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA solid state drives 2.5-inch bays: 2.5-inch SATA solid state drives |
| Hot-swappable | Yes The following are not hot-swappable: M.2 SSDs, SSD cache drives, SSDs using PCIe expansion slots. |
| M.2 Slot | 2 x M.2 2280 PCIe Gen 3 x4 slots Compatible with NVME PCIe Gen3 & Gen4 SSDs, refer to https://www.qnap.com/compatibility/ for compatibility The M.2 SSD is not included as standard. M.2 SSD operations can easily generate excessive heat. It is recommended to install a heatsink (from QNAP or a third-party provider) on the M.2 SSD. |
| SSD Cache Acceleration Support | Yes |
| SR-IOV | Yes |
| | |

| 2.5 Gigabit Ethernet Port (2.5G/1G/100M) | 2 (2.5G/1G/100M/10M) |
|---|---|
| 10 Gigabit Ethernet Port | 1 x 10GBASE-T |
| 25 Gigabit Ethernet Port | Optional via PCIe expansion card |
| Wake on LAN (WOL) | Yes |
| | Only the 2.5GbE port |
| Jumbo Frame | Yes |
| PCIe Slot | 2 Slot 1: PCIe Gen 3 x4 Slot 2: PCIe Gen 3 x4 |
| | Card dimensions for PCIe slot 1 : $150 \times 68.9 \times 18.76 \text{ mm} / 5.90 \times 2.71 \times 0.74 \text{ inches.}$ Card dimensions for PCIe slot 2 : $150 \times 68.9 \times 18.76 \text{ mm} / 5.90 \times 2.71 \times 0.74 \text{ inches.}$ |
| USB 2.0 port | 1 |
| USB 3.2 Gen 1 port | 3 |
| Form Factor | Tower |
| LED Indicators | Power/Status, LAN, USB, HDD1-6, SSD 1-2, M.2 SSD 1-2 |
| Buttons | Power, Reset, USB Auto Copy |
| Dimensions (HxWxD) | 231.9 × 292.9 × 319.8 mm |
| Weight (Net) | 8.5 kg |
| Weight (Gross) | 10.11 kg |
| Operating Temperature | 0 - 40°C (32°F - 104°F) |
| Storage Temperature | -20 - 70°C (-4°F - 158°F) |
| Relative Humidity | 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) |
| Power Supply Unit | 250W PSU, 100~240V |
| Power Consumption: Operating Mode, Typical | 86.96 W |
| | Tested with drives fully populated. |
| Fan | System fan: 2 x 80mm, 12VDC CPU fan: 1 x 90mm, 12VDC |
| Other Interfaces | Kensington security slot |
| System Warning | Buzzer |
| Kensington Security Slot | Yes |
| Standard Warranty | 3 |
| | |

Max. Number of 2500 Concurrent Connections (CIFS) - with Max. Memory

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting. QNAP reserves the right to replace partial parts or accessories if the original is no longer available from its manufacturer/supplier. Any replacement would be fully tested and verified to meet strict compatibility and stability guidelines and will deliver identical performance to the original.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.