



---

## 1080P Day & Night Auto Focus IR Vandal Resistant Dome IP Camera



---

### Features

- Full HD 2 megapixel CMOS image sensor
- 2MP H.265/HEVC and H.264/AVC high-performance video compression
- Simultaneous streaming of H.265 and H.264 encoded streams
- Auto focus with zoom / focus motorized lens
- Smart H.264/H.265 supported
- 3D noise reduction (MCTF)
- 2D WDR function
- HDR function up to 100dB
- Digital PTZ supported
- IVS supported
- Tampering / Motion / Network lost detection event function
- SMART event
- High efficiency IR LED, radiant distance up to 30m
- Day & Night (IR cut removable)
- ONVIF Profile S and Profile T supported
- IP67 rain and dust resistant

## Specifications

Model	Z3R6522X
Min. illumination/Low Light Mode (Colour)	Color : 0.02 Lux at F1.6 ; B/W : 0.003 Lux at F1.6 ; 0 Lux with IR LED ON
Starting Temperature	-10°C – +50°C (14°F – 122°F)
Operating temperature	-40°C – +50°C (-40°F – 122°F)
Storage temperature	-25°C – +60°C (-13°F – 140°F)
Operating humidity	0% – 90% RH
Power Supply	DC12V ±10% / PoE (IEEE 802.3af compliant)
Power Consumption	DC12V, 6.3W / PoE, 8.1W
Focal Length	2.8 – 8 mm (zoom / focus motorized)
Iris	F1.6
Iris Control	Fixed IRIS
Angle of View	95.1° (W) – 57.9° (T) (H) 52.0° (W) – 32.2° (T) (V) 111.5° (W) – 66.4° (T) (D)
Peak wavelength	850nm
Beam Spread	30°, 50°
Max IR distance	30M
Pick Up Element	1/2.8" CMOS image sensor
Effective pixels	1945 (H) × 1097 (V) = 2,133,665 (pixels)
Motion sensor	Wall, Ceiling, Pole
CE	Yes, EMI CLASS A
FCC	Yes, EMI CLASS A
IP Rating	IP67
Vandal Resistant Rating / IK Rating	IK10
CPU	Intel® Core™ i7 or higher grade
OS	Windows 7 or above
RAM	8GB or above, Dedicated Graphics Card
Web browser	Microsoft® Internet Explorer® 9 or above
Dimensions	Ø115 × 91 mm
Weight	435g

Casing Material	Aluminum alloy
Video Compression	H.265/HEVC main profile, H.264 main and high profile , Motion JPEG
Video streaming	RTP/HTTP, RTP/TCP, RTP/UDP, Multicast 4 configurable streams in H.265 and H.264 and Motion JPEG, configurable frame rate and bandwidth
Number of streams	4
Video bitrate	128Kbps – 12Mbps; Frame rate and bit rate controllable on-the-fly; VBR / CBR / GOP supported, Fixed bitrate, Smart H.264/H.265
Encryption	Base64 HTTP encryption, HTTPS encryption
Authentication	Digest HTTP authentication, RTSP authentication, 802.1x, DDNS via HTTPS
Address Filter	IP address filter, MAC address filter
Access	Multiple user access levels with password protection
User accounts	10 simultaneous users
Multi IP address	Yes
Resolution	2MP(1920 × 1080), 1.3MP(1280 × 960), 1MP(1280 × 720), D1(720 × 480, 720 × 576), VGA(640 × 480), CIF(352 × 240)
Maximum Frame Rate	Normal mode 60Hz: 30 fps @ 1920 × 1080 50Hz: 25 fps @ 1920 × 1080 HDR mode 60Hz: 30 fps @ 1920 × 1080 50Hz: 25 fps @ 1920 × 1080
Scanning System	Progressive Scan
Infrared Cut Filter	Auto / Day (Color) / Night (Mono) / Schedule
White Balance	ATW-NARROW / ATW-WIDE / AWC(MANUAL)
Back Light Compensation (BLC)	Yes
Electrical Shutter	1/30(1/25)s – 1/30000s
Sense Up+	Off / x2 / x4 / x8 / x16 / x32
Sense Up	Yes
Auto Gain Control	60 dB Variable Gain

S / N Ratio	More than 50dB (AGC off)
3D Noise Reduction	Off / 1 – 32 Selectable
2D WDR	Off / Auto / x2 / x3 / x4 (by normal mode) Support Onvif
High Dynamic Range(HDR)	Up to 100dB (by HDR mode, 2 shutter line interleave)
Privacy Masking	Off / On (4 zones)
Image Effects	Brightness, Contrast, Hue, Saturation, Sharpness, Mirror, Flip, Rotation, Overexposure Reduction
Auto Focus	One Push
EV (Exposure Value)	Adjustable
Lens distorsion correction (LDC)	Yes
Mobile Application	Integrated to LILIN mobile app (LILIN Viewer), iPhone, iPad, Android support
Video Management	ONVIF Profile S / ONVIF Profile T / IVS events, LILIN Navigator Enterprise 2.0 support, Third party VMS through LILIN HTTP API
Maintenance	Firmware update via HTTP and IP Scan; Firmware available at website
IVS Basic 1.0	Motion Detection, Tampering Detection, Advanced Motion Detection, Traffic Light Detection, Tripwire Detection, Object Counting
IVS Advanced 2.0 (Optional)	Motion Detection, Tampering Detection, Advanced Motion Detection, Traffic Light Detection, Tripwire Detection, Object Counting
IVS Advanced 2.1 (Optional)	Unattended Object Detection, Missing Object Detection, Crowd Detection, Loitering Detection, Face Detection
IVS Advanced 2.2 (Optional)	Detection Zone for Car and Human
Alarm event triggers	Motion / Tamper / Network lost detection / SmartEvent

Alarm event actions	FTP / SMTP / HTTP post / SAMBA / SNMP Trap / Push service notification
Languages	English, Traditional Chinese, Simplified Chinese, Spanish, Italian, Turkish, Russian, Korean, French, Arabic, Hungarian, Japanese
Network Interface/Ethernet	10/100 Mbps Base-T (Tx), RJ-45
ePTZ & Digital Zoom	Yes, ROI (Region of Interest)
OSD	Position configurable text overlay for date, time, camera ID, event status and watermark with customizable user demand data
CPU.Memory	Embedded SoC ARM Cortex-A9, 816MHz, 512MB DDR3L, 256MB flash memory
Network OS	Embedded Linux 3.10
Protocols	IPv4, IPv6, TCP, UDP, HTTP, HTTPS, SMTP, MQTT, QoS, SNMP V1/V2/V3, SNMP Trap and heart beat, NTP, DDNS, UPnP, FTP, ARP, DHCP, PPPoE, DNS, RTSP, RTCP, Telnet, ICMP, IGMP, ONVIF Profile S , ONVIF Profile T, SDDP, Bonjour , 802.1x, SSL/TLS
Max number of online users	10 simultaneous user
Video Display	LILIN Universal ActiveX , LILIN Java Applet
Watermark	BMP logo
Log	Event & operation log & IVS event log
Schedule	Support holiday list