

Kisi Reader Pro ^{KD-RP2.1}

The reader is a wall-mounted access control device used for easy access with smartphones or other credentials.

Key features

- Streamline access with Apple Wallet tap to unlock
- Integrate seamlessly with existing cabling with the use of the Kisi two-wire switch and adapter
- Receive over-the-air (OTA) updates that complete within seconds
- Get audio-visual feedback for unlock and other events
- Ensure offline support for both cards and phones
- Protected from weather and tampering

Credentials

Your current badges or adopt new ones

- Standardized credentials, including Bluetooth, NFC, and RFID
- Smartphones, Apple Passes, Kisi Passes, cards, and fobs
- MotionSense



Features

Operating temperature
-4°F to 122°F (-20°C to 50°C)
Weather resistant

Power connectivity
Power over Ethernet

Power consumption

- PoE Class 2 powered device with 6.49 watts maximum power consumption
- Maximum 0.5 amperes at 12 volts of direct current
- Maximum 0.25 amperes at 24 volts of direct current
- Idle power consumption less than 3 watts

User feedback
LED signaling

NFC
13.56 Mhz
Cards, tags and fobs

RFID
125 kHz
Cards and fobs
Formats supported:

- HID H10301 (26-bit card)
- HID H10302 (37-bit card)
- HID H10304 (37-bit card)
- HID D10202 (33-bit card)
- EM4100/TK4100 (26, 32, and 34-bit card)

Dimensions
Height: 4.84 in (12.3 cm)
Width: 1.97 in (5.0 cm)
Depth: 0.61 in (1.5 cm)

Optional backplate
Height: 5.83 in (14.8 cm)
Width: 2.95 in (7.5 cm)
Depth: 0.12 in (3 mm)

[Learn more](#)

[Wiring instructions](#)

getkisi.com



45 Main Street,
11201 Brooklyn
USA

sales@getkisi.com
getkisi.com

kisi