

ConteralP® Outdoor Dome Megapixel Camera

1080p or 5 Megapixel (MP) H.265/H.264 All-in-One Motorized Remote Focus and Zoom Varifocal Lens True Day/Night Indoor Dome IP Camera with SNAPstream+™ (Smart Noise Adaptation and Processing), Enhanced WDR™ (Wide Dynamic Range), NightView™, and Smart IR

H.265



The ConteralP® Outdoor Dome megapixel camera features 1080p and 5-megapixel (MP) resolution for optimum performance. The ConteralP Outdoor Dome combines a day/night mechanical IR cut filter with an integrated motorized remote focus and zoom varifocal lens for excellent, optimal image quality.

Regardless of the time of day, the ConteralP Outdoor Dome is prepared for any lighting condition. For applications with poor lighting conditions, Enhanced WDR™ (wide dynamic range) at 120dB provides the best visual balance to shaded and bright light conditions.

For clear color images in low-light, NightView™ offers strong low-light sensitivity for capturing details in extremely poor-lit scenes. Built-in Smart IR LED illumination automatically adjusts output in response to the distance of an object in view to prevent over-exposure when the object is very close to the camera.

AV Costar™ was the first to bring H.264 to the mainstream market and recently developed SNAPstream™ (Smart Noise Adaptation and Processing) technology

for reducing bandwidth without impacting image quality. Today we are proud to offer our next generation H.265 with SNAPstream+™ smart codec capable of delivering high quality video while saving over 50% of the data rate to reduce or prevent strain on the network.

The microSDXC card slot supports up to 1TB of capacity for convenient onboard storage. The camera's power can be supplied via a Power-over-Ethernet (PoE - IEEE 802.3af) compliant network cable connection. The ConteralP Outdoor Dome is IP66 rated for both indoor and outdoor applications. All models feature an impact resistant cast-aluminum housing.

The ConteralP Outdoor Dome is ONVIF (Open Network Video Interface Forum) Profile S, G, and T compliant, providing interoperability between network video products regardless of manufacturer.

| | | | | | | | | | |
|---|---|---|--|---|---|--|--|--|---|
|  Remote Focus and Zoom Lens (~200 Models Only) |  SNAPstream+™ Technology |  NightView™ |  Enhanced WDR™ Wide Dynamic Range |  Smart IR LEDs |  True Day/Night with IR Cut Filter |  CorridorView™ with 90° Image Flip |  H.264 H.265 MJPEG Tri-Encoder H.265/H.264/MJPEG |  1TB Max Capacity MicroSDXC Card Slot |  Impact / Weather Resistant IK-10 and IP66 Rated |
|---|---|---|--|---|---|--|--|--|---|

Series Features

- 1080p (2.1MP) or 5MP Resolution
- Remote Focus/Zoom Motorized Lens
- SNAPstream+™ Capability to Reduce Bandwidth without Impacting Image Quality
- NightView™ for Strong Low Light Performance
- True Day/Night Functionality with Mechanical IR Cut Filter
- Enhanced WDR up to 120dB at Full Resolution: See Clearly in Shaded and Bright Light Conditions Simultaneously
- CorridorView™ Allows 90° Image Rotation for Better Coverage in Hallways and Corridors
- Privacy Mask, Motion Detection, Bit Rate Control, Multi-Streaming, Multicasting, Forensic Zooming, and Scaling
- On-Screen Display (OSD)
- Triple Encoder: H.265/H.264/MJPEG
- Network Protocols Include SNMP, HTTPS, IPv6, DHCP, 802.1x, and More
- All-in-One H.265/H.264 Total PoE Solution, PoE and Auxiliary Power: 12V DC
- Smart IR Illumination with Variable Illumination Ensures that IR Light is Evenly Disbursed up to 82ft (25m) for Scenes with Low or No Ambient Light
- Audio In / Out
- 1TB Capacity MicroSDXC Card Slot for Onboard Storage
- Outdoor Rated IP66 and IK-10 Impact-Resistant Housing
- Easily Adjustable 3-Axis Gimbal
- NDAA Compliant

Camera Imaging Specifications

| Model | | AV02CLD-200 | AV05CLD-200 |
|--|------------------|---|---|
| Image Sensor | | 1080p (2.1MP) CMOS Progressive Sensor | 5MP CMOS Progressive Sensor |
| Optical Format | | 1/2.8" | 1/2.8" |
| Minimum Illumination | Color (Day Mode) | 0.04 Lux | 0.15 Lux |
| | B/W (Night Mode) | 0.005 Lux | 0.01 Lux |
| Full FOV Resolution | | 1920 H x 1080 V | 2592 H x 1944 V |
| Scaling <small>(See Scaling Resolutions Below)</small> | | Yes | Yes |
| IR Illumination | | 82ft (25m) max | 82ft (25m) max |
| Dynamic Range | | 120dB DOL WDR | 120dB DOL WDR |
| Frame Rates* | Single Stream | Up to 30fps (1080p) Enhanced WDR on; 60fps (1080p) off | Up to 30fps (5MP) |
| | Multi-Stream | Up to 60fps (1080p) + 60fps (1080p) + 60fps (360p) Enhanced WDR off Up to 30fps (1080p) + 30fps (1080p) + 30fps (360p) Enhanced WDR on | Up to 30fps (5MP) + 30fps (5MP) + 30fps (360p) Enhanced WDR off Up to 30fps (5MP) + 30fps (5MP) + 30fps (360p) Enhanced WDR on |
| Lens | | Motorized Lens 2.7–13.5mm, F1.4, H-FOV = 28°–100°, V-FOV = 16°–54° | 2.7–13.5mm, F1.4, H-FOV = 27°–79°, V-FOV = 20°–58° |

Programmability

| | | |
|----------------------------|---|--|
| Optics | Remote focus, remote zoom | |
| Low-Light Performance | NightView™ technology | |
| | Smart IR | |
| Programmable Shutter Speed | Auto/manual 0.1ms ~ 500ms | |
| Motion Detection | Real-time, 1024 detection zones | |
| Privacy Masking | Unlimited | |
| Backlight Compensation | Auto | |
| White Balance Mode | Auto/manual | |
| Gain Control | Auto | |
| Flicker Control* | 5Hz–255Hz adjustable | |
| Image Rotation | CorridorView™ (90°, 180°, and 270° image rotation) + mirror | |
| Scaling | 1080p | 1920x1080, 1280x720, 960x540, 640x480, 640x360 |
| | 5MP | 2592x1944, 2048x1536, 1920x1080, 1296x972, 1280x720, 960x540, 640x480, 640x360 |
| Wide Dynamic Range | Adjustment between WDR and LDR modes | |
| Efficiency | SNAPstream+™ (Smart Noise Adaptation and Processing) | |
| | Bit rate and bandwidth limitation control | |
| Miscellaneous | Programmable brightness, contrast, sharpness, saturation, hue | |
| Password | 16-digit ASCII character password | |
| On-Screen Display (OSD) | Time/date/camera name/custom text | |

Data Transmission

| | |
|------------------------|--|
| Compression Type | H.265/H.264 (MPEG-4, Part 10)/Motion JPEG |
| Bit Rate Control | 64K–8000K |
| Smart Codec | Smart GOP |
| Transmission Protocols | SNMP, HTTP, HTTPS, IPv6, IPv4, SSL, TCP/IP, UPnP, UDP, RTCP, RTSP, RTP, SMTP, NTP, DHCP, FTP, 802.1x, Zero Configure |
| | 10/100Base-T Ethernet network interface, RJ45 |
| Multi-Streaming | 2 x H.265/H.264 stream, 1 x M-JPEG stream |
| Users | Live viewing/Administrator for up to 10 clients |

Event Management

| | |
|---------------|--|
| Event Trigger | Motion detection, tampering detection, alarm in |
| Notifications | Send/record message via e-mail/FTP/NAS/SD card, record JPG/mp4 |

Compliance

| | |
|-------------------|--|
| Industry Standard | ONVIF Profile S, G, T conformant |
| Listings | UL (CB) UL60950-1, E489591 |
| FCC Compliance | 47 CFR 15 Class A |
| Environmental | RoHS, REACH, WEEE |
| Markings | (CE) EN55032 Class A, EN55024, EN61000-3-2, EN61000-3-3, EN60950 |
| Mechanical | IK-10 (EN62262), IP66 (EN60529) |

Environmental

| | |
|-----------------------|--------------------------------|
| Operating Temperature | -20°C (-4°F) to +50°C (122°F) |
| Humidity | 0% to 90% (non-condensing) |
| Storage Temperature | -40°C (-40°F) to +60°C (140°F) |

General Electrical

| | |
|---------------------|--|
| Alarm Input/Output | 1 input (wet contact)/1 output (wet contact) |
| Power Over Ethernet | PoE IEEE 802.3af, Class 3 |
| | Total PoE solution (no external power requirement) |
| Auxiliary Power | 12V DC |
| Power Consumption | 1080p 8.5W max |
| | 5MP 10W max |

IR Illuminator

| | |
|---------------------|----------------|
| LEDs | 4pcs, Smart IR |
| Projection Distance | 82ft (25m) max |

Audio Electrical

| | |
|--------------|------------------------|
| Streaming | Two-way |
| Compression | G.711 PCM 8 kHz/8 bit |
| Input/Output | Line in* / Line output |

* Requires Amplification

Mechanical


| | | |
|--|--|---|
| Casing | Die-cast aluminum chassis with polycarbonate dome bubble | |
| | IP66 weather proof standard | |
| | Impact resistant, IK-10 rated | |
| Gimbal | Easy 3-axis camera adjustment with 355° pan, and 60° tilt, and 180° Z-rotation | |
| Dimensions <i>(See Dimensions)</i> | Unit | Ø 5.55" (141mm) x 4.09" H (104mm) |
| | Packaged | 5.9" H (150mm) x 6.7" W (170mm) x 7.28" L (185mm) |
| Weight | Unit | 2.09lbs (0.95kg) |
| | Packaged | 2.16lbs (0.98kg) |
| On Board Storage | MicroSDXC slot up to 1TB (card not included) | |
| Body Color | AV Costar White (Pantone® Cool Gray 1C) | |

CLD-CAP-W



Mounting Cap

Dimensions



AV-PMJB-W



Pendant Mount Bracket with Standard Junction Box

CLD-FMA



Wall Mount Bracket with Standard Junction Box

AV-WMJB-W



Wall Mount Bracket with Standard Junction Box

See Next Page for Ordering Information



Model Numbers

| | | |
|--------------|-------------|------------|
| 1080p | AV02CLD-200 | WDR |
| 5MP | AV05CLD-200 | WDR |

Accessories (Sold Separately)

| | |
|------------------|---|
| AV-CRMA-W | Corner Mount Adapter (AV Costar White) |
| AV-PMA-W | Pole Mount Adapter (AV Costar White) |
| AV-PMJB-W | Pendant Mount Bracket with Standard Junction Box (AV Costar White) <i>(Fits Cap 1.5" NPT, Box Fits 3/4" NPT)</i> |
| AV-WMJB-W | Wall Mount Bracket with Standard Junction Box (AV Costar White) <i>(Fits Cap 1.5" NPT, Box Fits 3/4" NPT)</i> |
| CLD-CAP-W | Mounting Cap for ConteraIP Outdoor Dome (AV Costar White) |
| CLD-FMA-W | ConteraIP Outdoor Dome Flush Mount Adapter (White) |

Configurations



Surface mount dome

Create Your Model (Example: AV05CLD-200)

Megapixel Resolution Contera Product Line Body Type Generation Lens

