

FEATURES

- 16-Channel Hybrid DVR
- Compatible with AHD, TVI, CVI, and Analog Cameras
- 16Mbps IP Channel Throughput
- Bolide QuickConnect Mobile App
- Bolide VMS Software for PC and Mac



DVR SPECIFICATIONS

Recording Bandwidth

Inputs 16Mbps ~ 80Mbps
IP Bandwidth Max is 16Mbps,
Decrease One Analog Channel
Can Increase 4Mbps
(Default Decoding Performance
1080P 60FPS)

Output 80Mbps
Analog Video Input 16 Channels BNC

Live

IP Video Input 4 Channels
Composite Video In Up to 20 Channels (Analog+ IP)

Recording and Playback

Compression Audio: G.711a
Video : H.264/H.265

Display Resolution 1080N/720P/960H:30fps
IP:1080P/720P
Single IP Channel Preview up
to 2MP 30FPS Multi-Channel,
Preview Only Sub-Stream

Speed Main Stream:
1080N (960*1080):30FP
720P: 30FPS / Channel
IP: PAL:25FPS / Channel
NTSC: 30FPS / Channel

Sub-Stream:
PAL : 704*576: 10FPS / Channel
NTSC : 704*480: 10FPS / Channel



Playback 60FPS (Max 4CH Playback)
Playback Function Fast Forward / Backward
(2x, 4x, 8x,16x)
Slow Forward
(1/2x, 1/4x, 1/8x,1/16x)
Audio Yes, Audio Over Coax
Audio In/Out No
Video Output 1x HDMI
Ethernet 1x RJ45 10/100Base-T
USB 2x USB 2.0
HDD 1x SATA Up to 12TB
Dimensions 12.87" (L) x 8.25" (W) x 2" (H)

General

Dimensions 12.87in (L) x 8.25in (W) x 2in (H)
Voltage / Current 12VDC 2A
Power Consumption
(Excluding HDD) 4W
Operating Temp. 32°F ~ 104°F
Op. Humidity Less than 90%RH

Remote Access

Bolide QuickConnect App For iOS and Android

Bolide VMS For PC and Mac (Free Download)