



D-TECT Range Accessories



D-TECT WALK TESTER - GJD380

An installation tool to help set up D-TECT's on site


- Power 9VDC (PP3 Cell)
- Current Standby: 0.5mA
- Operating: 30mA
- Operating Temp: -20°C to +55°C



D-TECT CONDUIT CABLE ENTRY ADAPTOR - GJD304/ GJD304C

For surface mount conduit/cable installations. Complete with integral wall tamper system

- Suitable for 20mm conduit protected surface run cables
- Integrated rear tamper mechanism designed to perfectly interface with rear tamper plunger fitted on all D-TECT's
- Supplied with D-TECT body locking screws plus wall fixings



D-GUARD - (D-TECT, ELITE & OPAL) - GJD308

Steel wire plastic coated guard

- 26mm 2 steel wire mesh, plastic coated
- 180mm diameter
- 160mm deep
- 2 x fixing lugs with 8mm holes 225mm apart



POLE MOUNT BRACKET - (DETECTORS & CLARIUS) - PMB1

- Single Pole mounting bracket compatible with all Clarius Infra-Red & White-Light illuminators including SMB1, DMB1 and TMB1
- Supplied with stainless steel straps to fit 7.5 to 20 cm diameter pole
- Stainless steel construction



D-TECT X WIRELESS SIGNAL STRENGTH & WALK TESTER - GJD394

GJD's D-TECT X signal strength tester is an installation tool to aid the set up of D-TECT X wireless detectors. The tester measures signal strength from the detector at the receiver location and indicates if the detector is active by a simple walk test.

